

you need to modify the desktop file for PyCharm (the same procedure as for other IDE's). In Ubuntu 16.04 (and possibly earlier versions), you can edit the launcher file in either `/usr/share/applications` or `~/.local/share/applications` (depending on whether or not you installed PyCharm for all users). The launcher file may be called `pycharm-community.desktop` or `jetbrains-pycharm-ce.desktop`. Change the line that reads

- `1 Exec="/usr/lib/pycharm-community/bin/pycharm.sh" %f`
by adding `bash -i -c` at the beginning:
- `1 Exec=bash -i -c "/usr/lib/pycharm-community/bin/pycharm.sh" %f`

Packages

In order to work with packages just create a new project in the parent folder for all your packages or in a particular package. Please note that folder `.idea` with project files will be created. You can add it to `.gitignore` file in case if you are using Git and do not want to commit this file to repository. PyCharm will parse all files in the packages and allow you quick navigation, fast code completions, run and debug Python code, unittest run and debug.

Code

Code can be run using `roslaunch` or `roslaunch` command from the command line. Simple Python files can be run using run context menu.

In order to debug Python node do the following changes:

- Comment node in the launch file `my_nodes.launch`
- If the node has any parameters specified inside put them into `<group>` tag with `ns` attribute equal to node name
- Launch `my_nodes.launch` using `roslaunch` command
- Run Python node from PyCharm IDE in debug mode

Unittest

Unittest can be simply run using content menu on the file in the project tree or on a particular method in the code. Results would be shown in UI.

Unittest can be normally debug using start debug menu. In case of integration test (rostest):

- Comment `<test>` tag in the `my_file.test` launch file
- launch `my_file.test` using `roslaunch` not `rostest`
- launch test using PyCharm unittest debug from IDE