

- You will now find two Eclipse files in your package. It is not recommended to add them to the repository, as they contain absolute links and will be different for different users checking out your software.
- Note that if you change anything to your manifest.xml, you will have to run this script again, which will overwrite your Eclipse project file and thereby reverting all manual changes to the project settings.

Note: Simply running the cmake Eclipse generator like

- `1 cmake -G"Eclipse CDT4 - Unix Makefiles"`

will overwrite the Makefile. This can also happen if make eclipse-project does not complete successfully. If you already did this, you will want to restore the original Makefile, which should contain the following line:

- `1 include $(shell rospack find mk)/cmake.mk`

2. Creating eclipse files for multiple packages/stacks

Go to the directory where your packages reside (which may be a stack-folder or just a simple folder) and run:

- `1 rosmake --target=eclipse-project --specified-only *`

If you need to convert deeper nested packages or multiple stacks at once be encouraged to use this eclipse projects bash script (<https://gist.github.com/1098960>) for subdirectories.

3. Catkin-y approach

If you are using catkin, you do not have the possibility to use make eclipse-project. You need to execute:

- `1 catkin_make --force-cmake -G"Eclipse CDT4 - Unix Makefiles"`

to generate the .project file and then run:

- `1 awk -f $(rospack find mk)/eclipse.awk build/.project > build/.project_with_env &&& mv build/.project_with_env build/.project`

to pass the current shell environment into the make process in Eclipse.

After executing this command you will find the project files in the build/ folder. Now you can import your project as an existing project into the workspace.

Maybe you will need to execute the following if you would like to debug your program. To execute this command cd to the build/ folder. You should do so if you e.g. get an error like "No source available for main()".

- `1 cmake ../src -DCMAKE_BUILD_TYPE=Debug`