

- 4 PATH

The easiest way to obtain the correct values for your installation is to open a terminal and run

- 1 \$ echo \$ROS _ ROOT
- 2 \$ echo \$ROS _ PACKAGE _ PATH
- 3 \$ echo \$PYTHONPATH
- 4 \$ echo \$PATH

You should now be able to compile your package properly, for example by hitting CTRL-B (or selecting Project → Build project in the menu).

Note: When working with multiple projects, Eclipse won't be able to determine the correct build order or when dependent projects have to be rebuilt. You have to set the project interdependencies manually for each project in your workspace (see http://help.eclipse.org/belios/index.jsp?topic=/org.eclipse.cdt.doc.user/reference/cdt_u_prop_general_pns_ref.htm).

9. Running and debugging your executables within Eclipse

As for building within Eclipse, the crucial step here is to set the required environment variables correctly in the launch configuration. As the same for building, this should work out-of-the-box, especially if you follow Reusing your shell's environment from above.

Create a new launch configuration, right-click on the project, select Run → Run configurations... → C/C++ Application (double click or click on New). Select the correct binary on the main tab (Search project should work when your binary was already built). Then in the environment tab, add (at least)

- 1 ROS _ ROOT
- 2 ROS _ MASTER _ URI

again with the values of your installation. If you are unsure about them, open a terminal and run

- 1 \$ echo \$ROS _ ROOT
- 2
- 3 \$ echo \$ROS _ MASTER _ URI

Finally, if you cannot save the configuration, remove the @ character in the name of the new run configuration.

This should now allow you to run and debug your programs within Eclipse. The output directly goes into the Console of Eclipse. Note that the ROS_INFO macros use ANSI escape sequences, which are not parsed by Eclipse; therefore, the output might look similar to this one (from Writing a Publisher/Subscriber (C++)):