

delete, modify, or update the data. The commands for this are “INSERT,” “UPDATE” and “DELETE.”

7. Grant access to data

Developers can use SQL to provide access to other users. Developers use Design Control Language (DCL) for this. You can leverage certain commands “GRANT” and “REVOKE” to select which users have access.

SQL CHEAT SHEET <http://www.sqltutorial.org>



QUERYING DATA FROM A TABLE

SELECT c1, c2 FROM t;

Query data in columns c1, c2 from a table

SELECT * FROM t;

Query all rows and columns from a table

SELECT c1, c2 FROM t

WHERE condition;

Query data and filter rows with a condition

SELECT DISTINCT c1 FROM t

WHERE condition;

Query distinct rows from a table

SELECT c1, c2 FROM t

ORDER BY c1 ASC [DESC];

Sort the result set in ascending or descending order

SELECT c1, c2 FROM t

ORDER BY c1

LIMIT n OFFSET offset;

Skip offset of rows and return the next n rows

SELECT c1, aggregate(c2)

FROM t

GROUP BY c1;

Group rows using an aggregate function

SELECT c1, aggregate(c2)

FROM t

GROUP BY c1

HAVING condition;

Filter groups using HAVING clause

QUERYING FROM MULTIPLE TABLES

SELECT c1, c2

FROM t1

INNER JOIN t2 ON condition;

Inner join t1 and t2

SELECT c1, c2

FROM t1

LEFT JOIN t2 ON condition;

Left join t1 and t2

SELECT c1, c2

FROM t1

RIGHT JOIN t2 ON condition;

Right join t1 and t2

SELECT c1, c2

FROM t1

FULL OUTER JOIN t2 ON condition;

Perform full outer join

SELECT c1, c2

FROM t1

CROSS JOIN t2;

Produce a Cartesian product of rows in tables

SELECT c1, c2

FROM t1, t2;

Another way to perform cross join

SELECT c1, c2

FROM t1 A

INNER JOIN t2 B ON condition;

Join t1 to itself using INNER JOIN clause

USING SQL OPERATORS

SELECT c1, c2 FROM t1

UNION [ALL]

SELECT c1, c2 FROM t2;

Combine rows from two queries

SELECT c1, c2 FROM t1

INTERSECT

SELECT c1, c2 FROM t2;

Return the intersection of two queries

SELECT c1, c2 FROM t1

MINUS

SELECT c1, c2 FROM t2;

Subtract a result set from another result set

SELECT c1, c2 FROM t1

WHERE c1 [NOT] LIKE pattern;

Query rows using pattern matching %...

SELECT c1, c2 FROM t

WHERE c1 [NOT] IN value_list;

Query rows in a list

SELECT c1, c2 FROM t

WHERE c1 BETWEEN low AND high;

Query rows between two values

SELECT c1, c2 FROM t

WHERE c1 IS [NOT] NULL;

Check if values in a table is NULL or not

8. Analyze data manually

SQL lets developer analyze the data within the system manually. This is essential when developers need to intervene manually. You can use SQL queries to find the necessary data and then use it for analysis.

9. Combine datasets

The SQL Join function will let you simply combine data from two sets. Developers turn to this feature when they want to combine and compare two different tables.