

methods. In Windows OS, Chocolatey can be used to install or upgrade Dart. For example, to install Dart using Chocolatey, open the command prompt and type:

- `C:> choco install dart-sdk`

To upgrade Dart, type the following command:

- `C:> choco upgrade dart-sdk`

For Linux OS, there are different options available. One of them is to install using apt-get. Before installing, perform a one-time setup by running the following commands:

- `$ sudo apt-get update`
- `$ sudo apt-get install apt-transport-https`
- `$ sudo sh -c 'wget -qO- https://dl-ssl.google.com/linux/linux_signing_key.pub | apt-key add -'`
- `$ sudo sh -c 'wget -qO- https://storage.googleapis.com/download.dartlang.org/linux/debian/dart_stable.list > /etc/apt/sources.list.d/dart_stable.list'`

After the setup is complete, run the following commands to install Dart SDK:

- `$ sudo apt-get update`
- `$ sudo apt-get install dart`

Alternatively, you can also download the Dart SDK as a Debian package in the .deb package format and install it.

Modify Binaries

To gain access to all Dart binaries, modify the PATH after installing the SDK. In your active terminal session, you can use the following command:

For Linux and Mac OS:

- `$ export PATH="$PATH:/usr/lib/dart/bin"`

To change the PATH for future terminal sessions, use a command like this:

- `$ echo 'export PATH="$PATH:/usr/lib/dart/bin"' >> ~/.profile`

Installing Dart on Mac OS

For Mac OS, install Homebrew and then run the following commands:

- `$ brew tap dart-lang/dart`
- `$ brew install dart`

To upgrade when a new release of Dart is available:

- `$ brew upgrade dart`

The `main()` function is predefined and serves as the entry point to the application. In Dart, every script requires the `main()` method for code execution. Here's a basic example: