

Brand Model No.	ASUS P5N32-E SLI	ASUS Striker Extreme	Galaxy 680i LT SLI	XFX MB-N680-ILT9	Abit Fatal1ty FP-IN9 SLI	ASUS P5N-E SLI
						
Chipset	NVIDIA 680i	NVIDIA 680i	NVIDIA 680i LT	NVIDIA 680i LT	NVIDIA 650i SLI	NVIDIA 650i SLI
Socket	LGA 775	LGA 775	LGA 775	LGA 775	LGA 775	LGA 775
Northbridge	680i	680i	680i LT	680i LT	650i SLI	650i SLI
Southbridge	MCP55	MCP55	MCP55	MCP55	nForce 430i	nForce 430i
Price (Rs)	13,800	21,400	9,200	11,000	8,000	8,280
+	Great cooling solution	Very fast, great bundle	Well priced	Reasonably priced	Good overclocker	Good layout, price
-	Electrolytic capacitors	Very expensive	Skimpy bundle	Skimpy bundle	Build Quality	Ancient SLI switch
Grand Total (Out Of 100)	73.03	74.34	69.65	69.16	69.17	71.20
Features (Out Of 50)	32.48	34.45	27.44	27.89	26.40	28.24
Performance (Out Of 40)	37.25	37.76	37.26	37.13	37.07	37.46
Price (Out Of 10)	3.30	2.13	4.96	4.15	5.70	5.51
Features						
Front Side Bus Speed	1333 MHz	1333 MHz	1333 MHz	1333 MHz	1333 MHz	1333 MHz
Memory Type / Max Freq. Supported	DDR2 / 1066 MHz	DDR2 / 1066 MHz	DDR2 / 1066 MHz	DDR2 / 1066 MHz	DDR2 / 800 MHz	DDR2 / 800 MHz
Memory Supported / No. Of slots	8 GB / 4	8 GB / 4	8 GB / 4	8 GB / 4	8 GB / 4	8 GB / 4
No. Of SATA / PATA Ports	6 / 1	6 / 1	6 / 1	6 / 1	4 / 2	4 / 1
E-SATA Support / No. Of Ports	N / NA	N / NA	N / NA	N / NA	N / NA	Y / 1
Integrated Graphics (Y / N)	N	N	N	N	N	N
No. Of PCI / PCI x1 / PCI x4 Slots	2 / 2 / 1	2 / 2 / 1	2 / 2 / 0	2 / 2 / 0	2 / 2 / 0	2 / 1 / 0
Multi GPU Support (SLI / CrossFire / N)	SLI / x16 / x16	SLI / x16 / x16	SLI / x16 / x16	SLI / x16 / x16	SLI / x8 / x8	SLI / x8 / x8
Audio Controller / Channels / HD Compliant (Y / N)	ADI 1988B / 8 / Y	ADI 1988B / 8 / Y	Realtek ALC888 / 8 / Y	Realtek ALC888 / 8 / Y	Realtek ALC888/8/Y	Realtek ALC885 / 6 / Y
S/PDIF / Optical Port	Y / Y	Y / Y	N / Y	N / Y	N / Y	Y / N
No Of LAN Ports / Type (10/100 / Gigabit)	2 / G+G	2 / G+G	2 / G+G	2 / G+G	1 / G	1 / G
Integrated WiFi (Y / N)	N	N	N	N	N	N
No. Of Rear USB / FireWire Ports	4 / 1	4 / 1	4 / 1	4 / 1	4 / 1	4 / 1
All Solid State Capacitors (Y / N)	N	Y	N	N	N	N
Component Layout (Scale Of 10)	7.13	6.92	6.71	6.71	7.08	6.71
Overclocking Options						
CPU / FSB / Memory	Y / Y / Y	Y / Y / Y	Y / Y / Y	Y / Y / Y	Y / Y / Y	Y / Y / Y
Overvolting (CPU/Memory/FSB/PCIe/Northbridge)	Y / Y / Y / Y / Y	Y / Y / Y / Y / Y	Y / Y / Y / Y / Y	Y / Y / Y / Y / Y	Y / Y / Y / Y / Y	Y / Y / Y / Y / Y
CPU Voltage Range (Volts)	Upto 1.9v	Upto 1.9v	1.2-1.6V	1.2-1.6V	1.325-1.7v	0.83125-1.6v
Memory Voltage Range (Volts)	1.8-2.6v	1.8-2.6v	1.8-2.5V	1.8 ~ 2.5V	1.8-2.5v	1.92-2.517v
Package Bundle						
No Of SATA / PATA Cables	6 / 1	6 / 1	3 / 1	3 / 1	3 / 1	3 / 1
Software Bundle	NA	GRAV, 3D Mark 2006	NA	NA	NA	NA
Other Accessories	SLI Connector	Cooling Fans, USB Bracket	4 Port USB Bracket	USB Bracket, SLI Connector	SLI Connector, SLI Retention, FireWire Bracket	SLI Connector
Performance						
PC Mark 2005						
CPU	7526	7558	7521	7538	7522	7522
Memory / Graphics	6099 / 12874	6220 / 12652	6109 / 12013	6111 / 11968	6076 / 12706	6197 / 12738
HDD	7266	7251	7290	7195	7512	7033
Overall	8516	8556	8354	8362	8552	8560
SiSoft Sandra 2007						
CPU Arithmetic (Dhrystone / Whetstone)	27093 / 18764	27084 / 18783	27012 / 18751	27012 / 18754	27169 / 18637	27158 / 18728
CPU Multimedia (Integer / Floating)	161513 / 87931	161655 / 88038	161404 / 87870	161465 / 87901	161260 / 87743	161360 / 87882
Drive Index (MBps) / Random Access Time (ms)	84 / 8 ms	86 / 8 ms	79 / 8 ms	79 / 8 ms	70 / 8 ms	72 / 8 ms
Memory Bandwidth Score (Integer / Floating)	5707 / 5725	5770 / 5789	5752 / 5769	5746 / 5771	5661 / 5640	5874 / 5859
3D Mark 2005						
3D Marks / CPU Score	16934 / 9691	17084 / 10192	16982 / 9989	16946 / 9942	16981 / 9510	17103 / 10214
Real World Tests						
Video Encoding (DivX 6.2) 100 MB File	71.97 sec	70.76 sec	70.84 sec	72.53 sec	68.54 sec	70.71 sec
File Transfer - 4 GB File	52.98 sec	51.8 sec	52.25 sec	53.1 sec	53.47 sec	52.35 sec
Doom 3 (640x480 / 1600x1200, 4xAA, 4xAF)	237.6 / 118.7 fps	248.2 / 119.1 fps	242.1 / 118.3 fps	243.1 / 119.2 fps	231.4 / 118.8 fps	244.4 / 118.6 fps
Splinter Cell Chaos Theory (640x480 / 1600x1200)	229.8 / 118.4 fps	236.2 / 117.9 fps	232.6 / 117.9 fps	233.1 / 117.9 fps	231.4 / 117.2 fps	234.6 / 118.5 fps