

Read All

Refer to SNIPPET 5 from HERE <http://dgit.in/RealmSnippets>

The RealmResults object contains those Drop objects that satisfy some condition. In our case we have not specified any condition and thereby retrieve all the objects of type Drop stored in Realm. We can iterate over RealmResults like a simple ArrayList and process the data further.

Read all drops made by the person 'abc@gmail.com'

Use the equalTo method to specify the values which you would like to match for a particular field.

Refer to SNIPPET 6 from HERE <http://dgit.in/RealmCode>

Update

Update looks similar to any other write operation. Here are the following steps to perform an update

- Get an instance of the Realm class
- Begin the transaction
- Modify the object.
- Commit the transaction.

Update the email of the Person from 'abc@gmail.com' to 'def@gmail.com'

In the snippet below, we simply locate the first Person object whose email is 'abc@gmail.com' and update its value with the help of a setter method inside a transaction. If there are more than one people with the email 'abc@gmail.com' we would simply use the findAll method instead of findFirst which returns a RealmResults. We can loop through the RealmResults and call the setter method on each object.

Refer to SNIPPET 7 from HERE <http://dgit.in/RealmCode>

Delete

If you wish modify or delete any of the objects in a RealmResults, you must do so in a write transaction. Here are the steps to delete an item permanently from Realm.

- Get an instance of the Realm class
- Begin the transaction
- Delete one or more objects.
- Commit the transaction

Refer to SNIPPET 8 from HERE <http://dgit.in/RealmCode>

Transactions: How to persist changes?

In Realm, all write operations (adding, modifying, and removing objects) must be wrapped

*pointers

>>Interesting developer news

***Scrum Explained**

>>A simple tutorial explaining what Scrum is all about in under 7 minutes

<http://dgit.in/ScrumIn7>

***Realm course**

>> The author has published a certificate course that covers Realm DB for an Android app. This course is available on the Pyoopil App, use the code 'DIGIT' to get a 70% discount.

<http://dgit.in/PyoopilApp>

***Expressions and more**

>>This demo showcases Face2Face, a real time facial re-enactment tool from students of Stanford University

<http://dgit.in/Face2FaceTech>

***Interface for PI**

>>DIYer Toby Kurien implements Star Trek LCars interface into his Raspberry Pi Projects

<http://dgit.in/PIInterface>



in write transactions. A write transaction can either be committed or cancelled. During the commit, all changes will be written to disk, and the commit will only succeed if all changes can be persisted. By cancelling a write transaction, all changes will be discarded. Using write transactions, your data will always be in a consistent state.

Synchronous

So far we wrote synchronous transactions which can also be written in a different way. Instead of manually keeping track of realm.beginTransaction(), realm.commitTransaction(), and realm.cancelTransaction() you can use the realm.executeTransaction() method, which will automatically handle begin/commit, and cancel if an error happens. Let's take our earlier example of adding a drop to Realm and use a transaction block for the same.

Refer to SNIPPET 9 from HERE <http://dgit.in/RealmCode>

Asynchronous

By using an asynchronous transaction, Realm will run that transaction on a background thread and report back when the transaction is done. Use the overloaded executeTransaction method that takes one more parameter known as Callback which has two methods: onSuccess and onError where we can execute code depending on the outcome of the transaction.

Refer to SNIPPET 10 from HERE <http://dgit.in/RealmCode>

Queries: How to do operations on data?

Realm's query engine uses a Fluent interface to construct multi-clause queries. Queries in Realm are lazy in the sense that actual data is not copied unless it is needed.

Operators

We executed some pretty basic queries earlier like trying to find the person whose email is 'abc@gmail.com' Lets explore the operators in more depth.

Refer to SNIPPET 11 from HERE <http://dgit.in/RealmCode>

Some operators that you can use in place of contains would be between(), greaterThan(), lessThan(), greaterThanOrEqualTo(), lessThanOrEqualTo(), equalTo(), notEqualTo(), contains(), beginsWith() & endsWith() along with logical operators such as and(), or() and not()