

**STEP3.** Now add the following snippets in a script:

3a. Set the regression and tracker modules:

```
window.onload = function() {
  WebGazer.setRegression('weightedRidge')
  //different regression modules can
  be used.. Refer documentation
  .setTracker('clmtracker') //three trackers are
  available by default, refer documentation
  .setGazeListener(function(data, clock) {
    /* data: is an object containing an x and y
    key which are the x and y prediction coordinates
    (no bounds limiting) , clock: elapsed time in mil-
    liseconds since WebGazer.begin() was called */
  })
  .begin()
  .showPredictionPoints(true); /*
  shows a square every 100 millisec-
  onds where current prediction is */
}
```

3b. The Setup with the video in a frame can be done as follows:

```
var width = 320;
var height = 240;
var topDist = '0px';
var leftDist = '0px';

var setup = function() {
  var video = document.getElem
  entById("WebGazerVideoFeed");
  video.style.display = 'block';
  video.style.position = 'absolute';
  video.style.top = topDist;
  video.style.left = leftDist;
  video.width = width;
  video.height = height;
  video.style.margin = '0px';

  WebGazer.params.imgWidth = width;
  WebGazer.params.imgHeight = height;

  var overlay = document.
  createElement('canvas');
  overlay.id = 'overlay';
  overlay.style.position = 'absolute';
  overlay.width = width;
  overlay.height = height;
  overlay.style.top = topDist;
  overlay.style.left = leftDist;
  overlay.style.margin = '0px';

  var myCanvas=get('canvas');
  myCanvas.width=screen.width;
  myCanvas.height=screen.height;

  document.body.appendChild(overlay);
```

## \*pointers

>>Interesting PHP  
developer videos



### \*WebGazer Demo

>>A demonstration of WebGazer by Alexandra Papoutsaki, one of the developers of the library.

<http://dgit.in/WebGzer>



### \*Udacity Javascript

>>Udacity's extensive playlist on Object Oriented Javascript covering basics as well as moderate level concepts.

<http://dgit.in/JStutUda>



### \*Google I/O - V8

>>Seth Thompson, Associate Product Manager, Google talks about improvements to Chrome's V8 engine in processing Javascript.

<http://dgit.in/GooglV8>



### \*Generators in JS

>>All about Generators, also known as co-routines, which are pausable functions in JavaScript, used to manage async operations

<http://dgit.in/JSGens>



```
var cl = WebGazer.
getTracker().clm;

function drawLoop() {

  requestAnimationFrame(drawLoop);
  overlay.getContext('2d').
  clearRect(0,0,width,height);
  if (cl.getCurrentPosition()) {
    cl.draw(overlay);
  }
  drawLoop();
}
```

3c. Now let us check if Webgazer is ready and call the setup method as defined previously:

```
function checkIfReady() {
  if (WebGazer.isReady()) {
    setup();
  } else {
    setTimeout(checkIfReady, 100);
  }
}

setTimeout(checkIfReady,100);
};//The window.onload function
which we started in step 3a ends here
```

**STEP 4.** Optionally save the data into local web storage or clear it as you wish...

```
window.onbeforeunload = function() {
  WebGazer.end(); //Saves the
  data even if you reload the page.
  //window.localStorage.clear(); //
  Uncomment if you don't want to save
  data across different sessions
}
```

## Stopping the Webgazer and Creating a Heatmap

### STEP 1.

Define the stopTracker function that is called on clicking the button

```
/*Helper Function*/
function get(id) {
  return document.getElementById(id);
}

function stopTracking()
{
  WebGazer.end(); //Save Webgaze Data
  var dataset=JSON.parse(window.
  localStorage.WebGazerGlobalData); //
  Read Data from Local Webstorage
```