



Our Phones are Brainhacking us

Former google product manager Tristan Harris says that our smartphones are programmed to keep us all hooked. <http://dgit.in/BrainHakka>



Citrix races forward

The use of Citrix by Red Bull on the racing track shows that the company is not just limited to telecommunications. <http://dgit.in/citrixRB>

- **'f'** - Requires a character to be specified after the command. This command moves the cursor to the next occurrence of that character from the current position of the cursor. In the case below, typing **fg**, will move the cursor to "n" which is right before "g".
`string mystring = ("hello world");`
- **'/'** - Requires a string. Searches for the next occurrence of the specified string. After that, typing **'n'** will go to the next occurrence and **'N'** will go to the previous occurrence. This works similar to the "find" feature found in most editors. However, this command can take in regex as well. For those who don't know, regex is an acronym for regular expressions which is a standard syntax to depict patterns.
- **'\$'** - Moves to the end of line,
- **'0'** - Moves to the beginning of line.
- **'h,j,k,l'** - Moves left, up, down and right by one character from current position. The newer versions of Vim support the arrow keys, but these are recommended as they are in the home row.

The motions can be preceded by a number, which will repeat that motion that many times. For example, **5fa** will move the cursor to the 5th occurrence of 'a' from the current cursor position.

For the full list of motions, type **:h motion.txt**

The document is opened in Vim,

```
MediaPlayer song;
TextView MusicStatus;
@Override
protected void onCreate(Bundle savedInstanceState) {
    super.onCreate(savedInstanceState);
    setContentView(R.layout.activity_music_player);

    Toolbar toolbar = (Toolbar) findViewById(R.id.toolbar);
    setSupportActionBar(toolbar);
    MusicStatus = (TextView) findViewById(R.id.music_status);
    FloatingActionButton fab = (FloatingActionButton) findViewById(R.id.fab);
    fab.setOnClickListener(new View.OnClickListener() {
        @Override
        public void onClick(View view) {
            setAction("Action", null).show();
        }
    });
}

public void StartMusic(View view){
    song = MediaPlayer.create(MediaPlayer.this, "Naarish");
    MusicStatus.setText("Playing");
    song.start();
}

public void StopMusic(View view){
    song.stop(); MusicStatus.setText("Paused");
}
```

A typical Vim interface

therefore you can use the motions you learnt to navigate through the document. You can also get help for a specific command, like **:h w**

The above command will open the motion section of the docs and scroll to the definition of the **'w'** command.

Manipulation of text

Now that you know how to find your way through your code, let's find out how to edit text. The commands to manipulate text can be split into action, modifier and motion. It's alright if it's a bit overwhelming; we'll look into examples to clear the concept.

- Motion - We've already covered

this in the previous section. Motion specifies the text to be **manipulated**.


- Action - This module specifies the action that must be run on the text. The basic ones are -
 - **'d'** - delete. Deletions are stored to the clipboard. Hence, no dedicated cut function.
 - **'y'** - copy, the abbreviation was derived from yank. **'p'** pastes whatever has been copied
 - **'c'** - change, deletes the text and enters insert mode. The semantic is that it 'changes' the text.
- Modifier - modifiers extend the text specified from the motion. The

* VIMTERESTING ARTICLES



*List of Vim plugins

A website that keeps a list of the best Vim plugins.
<http://dgit.in/VimPlugins>



*7 habits of text editing

A feature explaining habits to keep for efficient text editing by the creator of vim, Bram Moolenaar himself.
<http://dgit.in/EditingProTips>



*Vim adventure

A brilliant video tutorial series by Derek Wyatt.
<http://dgit.in/VimTutorial>