

Interactivity is added to Web Apps by writing JavaScript functions and hooking them to the interface. You can add your own functions to the basic.js JavaScript file, automatically created for your project by WDE. Start by editing the index.html and adding a form with a text entry box:

```
<!DOCTYPE html>
<html>
  <head>
    <title>Greet</title>
    <meta http-equiv="Content-Type"
content="text/html; charset=UTF-8"
/>
    <script language="javascript"
type="text/javascript" src="basic.
js"></script>
    <link rel="stylesheet"
href="basic.css" type="text/css"/>
  </head>
  <body onload="init();">

    <!-- form to enter a name -->
    <form method="post"
action="index.html">
      <p><label for="name">Name</
label>: <input type="text"
name="name" id="name"/></p>
      <p><input
type="button" value="Greet"
onclick="greet();" /></p>
    </form>

    <!-- greeting will be displayed
inside this paragraph -->
    <p id="greetings"/>

  </body>
</html>
The button's onclick attribute
is set to the greet() callback,
which we add to basic.js:
function init() {
}
function greet() {
  var name = document.
getElementById('name').value;
  if (name != '')
    document.
getElementById('greetings').in-
nerHTML = "Hello " + name;
}
```

Open index.html in the simulator tab again. Enter your text in the text box and click on the Greet button to call



Fig. 3: Your customised greeting displayed

the JavaScript function and display a greeting, as shown in Fig. 3.

Debugging

WebSDK provides debugging for Web Apps running inside the simulator.

- Add a breakpoint to the basic.js file by double-clicking in the margin next to a line of code, as shown in Fig. 4 below.



Fig. 4: Double-click in the margin to add a breakpoint

- In the Project Explorer, inside the expanded project content, right-click on the index.html file and select Debug As > Web Application. This starts the application in the simulator, and switches WDE into debugging perspective. If the perspective doesn't change, go to the Window menu and select Open Perspective > Debug.
- Use the Web App in the simulator.

You should now see the Debug perspective, with a cursor at the breakpoint.

- When you've finished examining the state of the application, adding expressions etc., use the buttons along the top of the Debug view to continue, step etc. through the program.

Packaging

Web Runtime applications on MeeGo use the wgt packaging format: it's a zip file with configuration metadata in a config.xml file. The configuration follows the W3C Widget Packaging and Configuration specification.

It is very simple to create a wgt package from a project:

- Right-click on the name of your project in the Project Explorer and select Package Web app.
- The output file is called <your project name>.wgt.

Once you have created a wgt package, you can transfer it to your device and run it. WDE also has a Deploy Web app option, but requires Bluetooth.

Installing the Web App

To install the qt-web-runtime packages on the target MeeGo device:

```
$ zypper install qt-web-
runtime
```

Once the Web Runtime components are installed, install your new Web App:

```
$ sudo widgetinstaller <path
to .wgt file>
```

This creates a new .desktop file in /usr/share/applications/ for your

Web App.

Running the Web App

To run your Web App, click on its icon in the Applications zone; or, run it from the command line with:

```
$ webwidgetrunner <path to
.desktop file created in
previous step>
```

Now that was simple, wasn't it? 

**WIN A
MEEGO TABLET
AND AND OTHER
EXCITING PRIZES**

Presenting the **MeeGo App Mania** contest. Publish your **MeeGo app on Intel AppUpSM center** and **win prizes!** You can also **earn money** when your **apps** are **downloaded** from the **Intel AppUpSM center**. Visit **bit.ly/meegomania** to register and get details.

Contest closes on July 27, 2011

- When you perform an action which will cause the code at the breakpoint to be executed (in this case, clicking the button), the simulator pauses and passes focus back to WDE. WDE may prompt you to confirm the switch to the Debug perspective: tick the Remember my decision box and click Yes, so that the perspective automatically switches in future.