

	Under ₹20,000						
Brand	Intel	Gigabyte	ASUS	MSI	Biostar	ASRock	
Model No.	DX79SI	GA-X79-UD3	Rampage IV Gene	X79A – GD45-8D	TPOWER X79	X79 Extreme 6	
Warranty (no. of months)	36	36	36	36	36	38	
Price (in ₹)	17000	17500	18650	18900	18900	18999	
Specifications (Out of 50)	25.6	25.95	30.6	28.55	29.8	32.5	
Overclocking and BIOS Options (Out of 25)	0	12.5	17.5	16.25	10	8.75	
Board Layout (Out of 20)	12.8	12.95	12.95	12.5	12.21	13	
Package Bundle (Out of 5)	1.9	1.7	2.1	2.1	2.1	4	
Grand Total (Out of 100)	40.9	53.1	63.15	59.4	54.11	58.25	
Specifications							
Max. Memory Supported (GB) / DIMMs	64 / 8	32 / 4	32 / 4	64 / 8	32 / 4	64 / 8	
No. of SATA 2 / SATA 3 Ports	4	4	2	04/02/12	3	4	
No of SATA 3 Ports	2	6	4	2	4	5	
No. of PCI Express 2.0 / 3.0 x16 graphics slots	0 / 3	0 / 4	0 / 3	2 / 3	0 / 3	0 / 3	
No. of PCI / PCIe x1 / PCIe x4	1 / 2 / 0	1 / 2 / 0	0 / 0 / 1	0 / 1 / 0	1 / 2 / 0	2 / 1 / 0	
Multi GPU (SLI/CrossFire) Support	Y / Y	Y / Y	Y / Y	Y / Y	Y / Y	Y / Y	
Optical / Coaxial S/PDIF Port	Y / N	Y / Y	Y / N	Y / Y	Y / Y	Y / Y	
No of LAN Ports	2	1	1	1	1	1	
On-board Wi-Fi (Y/N)	N	N	N	N	N	N	
No. of ports - USB 2.0 / USB 3.0	6 / 2	8 / 2	7 / 2	6 / 2	2 / 6	4 / 4	
No. of ports - FireWire / eSATA	1 / 0	0 / 2	0 / 1	0 / 0	0 / 1	1 / 1	
No of Fan Connectors	4	5	5	5	3	6	
Clear CMOS Button	Y	N	Y	Y	Y	Y	
All Solid State Caps (Y/N)	Y	Y	Y	Y	Y	Y	
Power and Reset Buttons (Y/N)	Y	N	Y	Y	Y	Y	
UEFI BIOS (Y/N)	N	Y	Y	Y	Y	Y	
USB 2.0 header	4	3	2	2	2	3	
USB 3.0 Header	1	1	1	1	1	1	
POST error code LED	Y	N	Y	N	Y	Y	
Dual BIOS	N	Y	Y	Y	N	N	
USB Charger	N	Y	Y	Y	Y	Y	
Form Factor	ATX	ATX	M-ATX	ATX	ATX	ATX	
Overclocking and BIOS Options							
Overclocking button	N	N	N	Y	N	N	
Overclocking Utility	N	Y	Y	Y	Y	Y	
Overclocking via Bluetooth	N	N	Y	N	Y	N	
Voltage check points	N	N	Y	Y	N	N	
Keyboard shortcuts	N	Y	Y	N	N	N	
Preset options (Energy saving, Normal, Overclocked)	N	N	Y	Y	N	N	
Separate home page	N	Y	Y	Y	N	N	
Board Layout							
Region around the CPU	7	7	7	7	7	7	
Location of SATA ports	8.5	8.5	7	8.5	7	7	
Placement of Memory modules	7	6	6.5	7	8	8	
Graphics card slot and PCI slots	7	8	7	6	8	7	
VRM Heatsink Quality	6	6	8	7	5.5	7	
Southbridge heatsink quality	7.5	7	7	6.5	5.5	8	
No of 8-pin CPU power connectors	1	1	1	1	2	1	
PCIe switches (Y/N)	N	N	N	N	N	N	
Package Bundle							
No of SATA cables	4	2	6	6	6	5	
I/O Shield	Y	Y	Y	Y	Y	Y	
USB 3 Bracket	N	N	N	N	N	Y	
eSATA Bracket	N	N	N	N	N	N	
CrossFire / SLI Bridge	Y / Y	Y / Y	Y / Y	N / Y	Y / Y	Y / Y	
Bundled Sound card	N	N	N	N	N	Y	
Performance							
AIDA64							
Memory							
Read(MB/s)	16067	16214	16417	16217	14723	16281	
Write(MB/s)	15057	15044	15113	15103	12780	15104	
Latency (ns)	61.7	61.2	59.3	60.2	63.7	60.9	
Cinebench R11.5							
OpenGL	79.55	79.54	79.43	79.63	70.64	80.14	
CPU (All cores)	10.52	10.5	10.38	10.19	9.64	10.45	
3D Mark 11 (1920x1080, Extreme)							
Graphics	2485	2448	2487	2488	2491	2487	
Physics	12228	12564	12335	12278	11430	12337	
Overall	2746	2749	2749	2750	2748	2749	
WinRAR 4.0 (Multi threaded) (KB/s)	4108	4024	4204	4134	3936	4218	
100 MB file Video Encoding (VOB-DivX 7) (sec)	17.91	19.45	18.16	18.06	19.48	18.11	
USB 3.0 Transfer (in MB/s)							
Sequential Write / Read	71.16 / 115.45	72.24 / 114.58	71.65 / 114.63	71.34 / 115.02	72.93 / 112.43	70.8 / 114.23	
Assorted Write / Read	43.31 / 104.51	42.21 / 102.24	42.12 / 100.58	43.7 / 100.71	43.11 / 100.32	41.23 / 101.21	
Game (in FPS)							
Resident Evil 5 (1920x1080, 8xAA, High)	172.4	172.4	173.1	169.5	166.8	169.1	
FarCry2 (1920x1080, 8xAA)	104.23	103.25	104.31	102.05	103.17	102.23	