

Brand	Fujifilm		Olympus		
Model	X-Pro1	X-E1	OM-D E-M5	PEN E-PL5	
Price (₹)	1,04,999	92,698	77,990	44,990	
Features (Out of 20)	13.24	13.56	14.44	13.02	
Still Image Performance (Out of 40)	33.22	33.66	29.72	29.2	
Video Performance (Out of 30)	21.75	22.14	23.19	20.7	
Build Quality (Out of 5)	4.63	4.63	4.25	3.75	
Ergonomics and usability (Out of 5)	4.4	4.45	4	3.85	
Grand Total (Out of 100)	77.24	78.44	75.6	70.52	
Specifications					
Sensor resolution (megapixel)	16	16	16	16	
Sensor size (mm)/Type	1.5-inch/X-Trans CMOS	1.5-inch/X-Trans CMOS	4/3-inch/CMOS	4/3-inch/CMOS	
Image Processor	EXR Pro	EXR Pro	TruePic VI	-	
Viewfinder type	OVF/EVF	EVF	EVF	Optional	
ISO low/high/Hi-Mode	200/6400/25600	200/6400/25600	200/25600/-	200/25600/-	
Auto Focus system	Contrast Detect AF	Contrast Detect AF	Contrast Detect AF	Contrast Detect AF	
Manual Focus (Y/N)	Y	Y	Y	Y	
Focal Length Multiplier	1.5x	1.5x	2x	2x	
White balance presets	7	7	12	8	
Built-in Flash (Y/N)	N	Y	N	N	
External Flash provision	Y	Y	Y	Y	
Flash Sync Speed	1/180 sec	1/180 sec	1/250 sec	1/250 sec	
Exposure Compensation Range	±2 (at 1/3 EV steps)	±2 (at 1/3 EV steps)	±3 (at 1/3 EV, 1/2 EV, 1 EV steps)	±3 (at 1/3 EV, 1/2 EV, 1 EV steps)	
Metering Modes	Multi, average, Spot	Multi, average, Spot	Multi, Center Weighted, Spot	Multi, Center Weighted, Spot	
Aperture/Shutter priority (Y/N)	Y/Y	Y/Y	Y/Y	Y/Y	
AE Bracketing (Y/N)	(at 1/3 EV, 2/3 EV, 1 EV steps)	(at 1/3 EV, 2/3 EV, 1 EV steps)	(2, 3, 5, 7 frames at 1/3 EV, 1/2 EV, 2/3 EV, 1 EV steps)	(2, 3 frames at 1/3 EV, 1/2 EV, 2/3 EV, 1 EV steps)	
WB Bracketing (Y/N)	No	No	Yes (3 frames in 2, 4, 6 steps selectable in either blue/amber or magenta/green axis)	Yes (3 frames in 2, 4, 6 steps selectable in either blue/amber or magenta/green axis)	
Continuous Drive (frames per second)(at max resolution)	6	6	9	8	
LCD size (inches)/LCD Resolution (dots)	3-inch/1,230,00	2.8-inch/460,000	3-inch/610,000	3-inch/460,000	
LCD Articulated/LCD Touchscreen(Y/N)	N/N	N/N	N/Y	N/Y	
Microphone type	Stereo	Stereo	Stereo	Stereo	
Max Video capture resolution	1920x1080	1920x1080	1920x1080	1920x1080	
Battery Type (AA, Li-ion)	Li-ion	Li-ion	Li-ion	Li-ion	
Battery Life (Manuf rated no. of shots)	300	350	360	360	
Memory cards used	SDXC	SDXC	SDXC	SDXC	
Body dimensions (in mm)	140 x 82 x 43 mm	129 x 75 x 38 mm	122 x 89 x 43 mm	111 x 64 x 38 mm	
Weight (in grams)	240	350	392	194	
Performance ISO					
Toy Fibers					
ISO 1600	9	9	8	8	
ISO 3200	9	9	7	7	
Labels					
ISO 1600	9	9	8	8	
ISO 3200	9	9	7	7	
Scene Test					
Dynamic Range	8.5	9	7.5	7.5	
Color Saturation	8.5	9	8.5	7.5	
Contrast	7	8	8	8	
Central Sharpness	8.5	8.5	7.5	8	
Corner Sharpness	7	7	6.5	7	
Video Quality					
HD Indoor focussing/Noise Suppression	7 / 8	7 / 8	8 / 8	6 / 7	
HD Outdoor shoot Dynamic Range	8	8	7	7	
HD Outdoor shoot Saturation	6	8	8	8	
HD Outdoor shoot Subject Tracking	6	7	8	7	
HD Outdoor shoot Audio Quality	6	6	7	7	