

theory behind this is that a Java “applet” is really content such as graphics, rather than full application software. However, as of July, 2000, all known browsers have had bugs in their Java virtual machines that would allow hostile applets to break out of this sandbox and also access other parts of the system. As a matter of fact, most security experts browse with Java disabled on their computers, or encapsulate it with further sandboxes/virtual-machines.

Hostile Script

A script is a text file with a .VBS, .WSH, .JS, .HTA, .JSE, .VBE extension that is executed by Microsoft WScript or Microsoft Scripting Host Application, interpreting the instructions in the script and acting on them. A hostile script performs unwanted actions.

HTTP Server

When installed without user awareness, an HTTP server allows an attacker to use a Web browser to view and thus retrieve information collected by other software placed in the user’s machine.

Hole

Vulnerability in the design software and/or hardware that allows circumvention of security measures.

Host

A term often used to describe the computer file to which a virus attaches itself. Most viruses run when the computer or user tries to execute the host file.

Impact

The extent to which an attacker may gain access to a system and the severity of it on the organisation.

IRC War

Any tool that uses Internet Relay Chat for spoofing, eavesdropping, sniffing, spamming, breaking passwords, harassment, fraud, forgery, electronic trespassing, tampering, hacking, nuking, system contamination including without limitation use of