

controlled by the attacker or could be programmed to strike like a logic bomb—starting on a specific day or at specific hour.

- **Denial of Service (DoS) Attack Trojans:** The main idea behind this kind of Trojan is to generate a lot of Net traffic on the victim's machine, to the extent that the Internet connection is too overloaded to let the user visit a Web site or download anything. Another variation of a DoS Trojan is the mail-bomb Trojan, whose main aim is to infect as many machines as possible and simultaneously attack specific e-mail addresses with random subjects and contents that cannot be filtered.
- **Proxy/Wingate Trojans:** These types of Trojan turn the victim's computer into a proxy/wingate server. That way, the infected computer is available to the whole world to be used for anonymous access to various risky Internet services. The attacker can register domains or access pornographic Web sites with stolen credit cards or do similar illegal activities without being traced.
- **FTP Trojans:** These trojans are probably the most simple, and are outdated. The only thing they do is open port 21—the port for FTP transfers—and let everyone connect to your machine. Newer versions are password-protected, so only the attacker can connect to your computer.
- **Software Detection Killers:** These trojans kill popular antivirus/firewall programs that protect your machine to give the attacker access to the victim's machine.

A trojan could have any one or a combination of the above mentioned functionalities.

Worms: Computer Worms are programs that reproduce and run independently, and travel across network connections. The main difference between viruses and worms is the method in which they reproduce and spread. A virus is dependent upon a host file or boot sector, and the transfer of files between machines to spread, while a worm can run completely independently and spread of its own accord through network connections.