

DTIM

Delivery Traffic Indication Message. A DTIM is a signal sent as part of a beacon by an access point to a client device in sleep mode, alerting the device to a packet awaiting delivery.

DTIM Interval

A DTIM interval, also known as a Data Beacon Rate, is the frequency at which an AP's beacon will include a DTIM. This is usually measured in milliseconds, or its equivalent, kilomicroseconds (Kμsec).

Dual-band Radio

A radio device is dual-band if it can send and receive signals from two frequencies—in the case of wireless networking, both the 2.4 GHz and 5 GHz bands.

Dynamic DNS

The DNS would quickly run out of IP addresses if every Web-browsing computer user in the world were assigned a permanent one. Dynamic DNS is the system by which ISPs or companies are assigned a pool of IP addresses that they can assign to any user only for the time needed, so the same IP addresses can be used repeatedly for different people in different sessions.

EAP

Extensible Authentication Protocol. When you log on to the Internet, it's most likely that you are establishing a Point-toPoint Protocol (*see PPP*) connection via a remote access server. The password, key, or other device you use to prove that you are authorized to do so is controlled via PPP's Link Control Protocol (LCP). LCP is somewhat inflexible, however, because it has to specify an authentication device early in the process. EAP lets the system gather more information from the user before deciding which authenticator to use. It is called extensible because it allows more authenticator types than LCP did, such as passwords, public keys, or biometrics.