

contact connector, Slot 2 uses a wider 330-contact connector. The biggest difference between Slot 1 and Slot 2 is that the Slot 2 design allows the CPU to communicate with the L2 cache at the CPU's full clock speed; in contrast, Slot 1 only supports this communication at half the CPU's clock speed.

ACPI (Advanced Configuration and Power Interface)

A power management specification developed by Intel, Microsoft, and Toshiba. ACPI enables the OS to control the amount of power given to each device. With ACPI, the operating system can turn off peripheral devices such as a CD-ROM players when they are not in use. ACPI also enables a computer to automatically power up as soon as you touch the keyboard, if it has been designed that way by the manufacturer.

APM (Advanced Power Management)

An API developed by Intel and Microsoft that allows developers to include power management in BIOSes. APM defines a layer between the hardware and the OS which effectively shields the programmer from hardware details. APM is expected to be gradually replaced by ACPI.

ECP (Extended Capabilities Port)

A parallel port standard for PCs that supports bi-directional communication between the PC and attached devices, such as a printer. ECP is about 10 times faster than the older Centronics standard. See also EPP.

EPP (Enhanced Parallel Port)

A parallel port standard for PCs that supports bi-directional communication between the PC and attached devices, such as a printer. EPP is about 10 times faster than the older Centronics standard. EPP can support several devices in a daisy chain formation. See also ECP.

Form Factor

The physical layout of a motherboard in regards to the relative