

sage to one or more recipients. MMS addresses can be either phone numbers of other users capable of receiving an MMS or e-mail.

The initial submission by an MMS client to the home MMS Center (MMSC) is accomplished using HTTP with specialised commands and encoding. Upon receiving the MMS message, the recipient MMSC (MMS Center) sends a notification to the recipient's mobile phone using either an SMS notification, HTTP Push or WAP Push.

There are two modes of delivery in MMS, immediate and deferred.

- 1. Immediate delivery:** When the MMS client on the mobile phone receives the MMS notification, it immediately (without user intervention or knowledge) retrieves the MMS message from the MMSC that sent the notification. After retrieval, the subscriber is alerted to the presence of a newly-arrived MMS message.
- 2. Deferred delivery:** The MMS client alerts the subscriber that an MMS message is available, and allows the subscriber to choose whether and when to retrieve the MMS message. As with the MMS submission, the MMS retrieval request, whether immediate or deferred, occurs with an HTTP request. The MMSC responds by transmitting the MMS message in an HTTP response to the MMS client, after which the subscriber is alerted that the MMS message is available.

MMS-enabled mobile phones enable subscribers to compose and send messages with one or more multimedia parts. Mobile phones with inbuilt cameras or MP3 players are very likely to also have an MMS messaging client—a software program that interacts with the mobile subscriber to compose, address, send, receive, and view MMS messages.