

/i: (Used only with NTFS) Performs a less vigorous check of index entries, reducing the amount of time needed to run `chkdsk`.

/c: (Used only with NTFS) Skips the checking of cycles within the folder structure, reducing the amount of time needed to run `chkdsk`.

/l[:size]: (Used only with NTFS) Changes the log file size to the size you type. If you omit the size parameter, `/l` displays the current size.

/?: Displays help at the command prompt.

9.5.3 Running Chkdsk

- m To run `chkdsk` on a fixed disk, you must be an Administrator.
- m If you want `chkdsk` to correct disk errors, you cannot have open files on the drive. If files are open, the following error message appears:

“Chkdsk cannot run because the volume is in use by another process. Would you like to schedule this volume to be checked the next time the system restarts? (Y/N)”

If you choose to check the drive the next time you restart the computer, `chkdsk` checks the drive and corrects errors automatically after you restart the computer. In addition, if the drive partition is a boot partition, `chkdsk` automatically restarts the computer after it checks the drive.

- m `Chkdsk` examines disk space and disk use for the FAT and NTFS file systems. It provides information specific to each file system in a status report. This status report shows errors found in the file system.
- m If you run `chkdsk` without the “/f” switch on an active partition, it might report spurious errors because it cannot lock the drive.