

Bank Interleave

Options: Disabled, 2-Way, 4-Way

Recommended Setting: Depends on the memory modules you have.

Explanation: Interleaving requests to different RAM banks can give you a performance boost. 64 MB and lower RAM modules have two banks. Larger modules have four banks. Check your RAM modules and decide.

Data Integrity Mode

Options: ECC, Non-ECC

Recommended Setting: ECC

Explanation: Both the chipset (motherboard) and the RAM have to support ECC. If you don't know, then it should be set to Non-ECC.

Delay DRAM Read Latch

Options: Auto, No Delay, 0.5ns, 1.0ns, 1.5ns

Recommended Setting: Depends on the memory modules you have.

Explanation: Tweaks for high RAM loads. Two-sided 256MB modules are high-load, one-sided memory modules are not. For lower RAM loads, set it at No Delay. For high RAM loads, you need to increase the delay. If you are getting crashes after you install new RAM, this is the first place to look.

DRAM CAS Latency Time / DRAM Cycle Length

Options: 2, 2.5, 3

Recommended Setting: Depends on the memory modules you have.

Explanation: CAS latency is part of the wait between the chipset requesting data and the RAM modules getting ready to send it. Shorter delays are better. A lower number is therefore better if your RAM is able to handle it. 2.5 is only available with DDR RAM.

Fast R-W Turnaround

Options: Enabled, Disabled

Recommended Setting: Depends on system stability

Explanation: When the CPU switches from reading to writing