

there is a delay. Enabling it reduces the delay. Disable it if it causes system instability.

Force 4-Way Interleave

Options: Enable, Disable

Recommended Setting: Disabled

Explanation: This is supposed to force the chipset to use 4-way interleave even if it does not detect it. The chipset will most likely turn on 4-way interleave if it is specified in the Bank Interleaving setting, so you can leave this disabled.

MD Driving Strength/Memory Data Drive

Options: Low, High

Recommended Setting: Depends on the memory modules you have.

Explanation: Change from low to high if the signal strength, under high RAM Load, is insufficient. Changing this setting may affect system stability.

Read Around Write

Options: Enabled, Disabled

Recommended Setting: Enabled

Explanation: Out-of-order read-write commands result in higher performance.

Read Wait State/Read Latency

Options: 0, 1

Recommended Setting: 0 if there is no instability.

Explanation: When a device reads from the RAM, the chipset holds the data for one cycle. Setting it to zero cycles increases performance, but the device may not be ready to receive the data—resulting in instability.

Refresh Interval/Refresh Mode Select

Options: 7.8 μ sec, 15.6 μ sec, 31.2 μ sec, 64 μ sec, 128 μ sec

Recommended Setting: 128 μ sec; depends on the memory modules you have.