

```
/etc/sysconfig/network-scripts/ifcfg-eth0
```

DEVICE=eth0	-The primary Ethernet card
BOOTPROTO=None	
BROADCAST=10.10.124.255	-Broadcast address
HWADDR=00:0B:2B:0C:49:9A	-MAC address of your Ethernet card
IPADDR=10.10.124.28	-Your IP address
NETMASK=255.255.255.0	-Subnet mask
NETWORK=10.10.124.0	-Network your machine is in
ONBOOT=no	-Start Network on boot
TYPE=Ethernet	-Type of card
USERCTL=no	
PEERDNS=yes	
GATEWAY=10.10.124.1	-Gateway address
IPV6INIT=no	-Initialise IP version 6 (always 'no')

```
/etc/sysconfig/network
```

NETWORKING=yes	-Enable Networking (does not mean start on boot)
HOSTNAME=aryan	-Name of your machine (Computer Name)

```
/etc/hosts
```

```
# Do not remove the following line, or various programs
# that require network functionality will fail.
127.0.0.1    aryan localhost.localdomain localhost
```

7.3 Browsers

Linux comes with default browsers. Yes, we mean more than one browser. Most distributions normally have a main, default browser and a browser that is a part of the desktop environment—KDE and GNOME. Konqueror doubles up as the file explorer as well as an Internet browser on KDE, whereas Nautilus, a file explorer, doubles up as a browser for the GNOME desktop.

The main browser for any desktop environment, and almost all distributions, is Mozilla. Newer distributions use Firefox, whereas older ones running kernel 2.4.x have the older Mozilla browser. Apart from these, other browsers such as Opera, Galeon (for