

their Web site. But at the end of our explanation you will know how easy it is! Moving on to the next step—creating symbolic links to your current plug-ins. It will better to switch to root user than using `sudo` all the time. `Sudo` will be necessary for Ubuntu users, but they can choose to open a root terminal instead of the normal GNOME-terminal.

Creating links to current plugins

```
cd /usr/more-apps/firefox/plugins
```

```
ln -s /usr/lib/mozilla-1.7.3/plugins/* . Or
```

```
ln -s /usr/lib/firefox-0.10.1/plugins/* .
```

Whenever you click on the Firefox button, or type in “firefox” at the command line, the old version of the browser pops up. So, to ensure that only the new Firefox opens and not the earlier version, you need to change the symbolic link that relates to the action of opening the browser. Use the “which” command to figure out the path to Firefox. Change your directory to the directory where “firefox” is located. Rename the old “firefox” file from “firefox” to “firefox.old”.

Setting firefox to run the new Firefox 1.5

```
#which firefox
```

```
output: /usr/bin/firefox
```

```
#cd /usr/bin
```

```
#mv firefox firefox.old
```

```
#ln -s /usr/more-apps/firefox/firefox
```

Click on the button that opens Firefox, or rather, just open from the command line (as you’re still in it) by typing in “firefox” and hitting [Enter]. In the browser that opens, go to Help > About Mozilla Firefox. This should show you “Firefox version 1.5.0.1”.

You can add extensions to your browser from Mozilla’s site (www.mozilla.com/extensions/). Browse through various extensions available on their site and choose the ones you like. Firefox