

We at *Digit* congratulate him on his success.

Download the script from the site mentioned above. The download link may open as a text file in the browser itself. Save this page to you PC. Use CLI to change this Bourne Shell Script to an executable script:

```
#chmod 700 SYSINFOV2.3 + [Enter]
```

To run the script:

```
#,/SYSINFOV2.3 + [Enter]
```

The script tries to run the GUI implementation and if it fails, it falls to the text mode. In either case you will get system information.

9.4 Upgrading Software ? YUM, APT-GET

Linux is an operating system that is in the constant process of updates and patches. Manually updating all machines can be a daunting task for a system administrator. Thankfully the user or administrator need not manually check for and download updates. Linux has a provision of automatically updating selective or all packages using what are called Package Managers. The Package Managers have a database of the software installed, their version, the Internet address from where an update can be obtained, etc. rpm-based Linux flavours generally use the yum package manager while the Debian-based ones use apt-get. These are basically command-line means of updating—it involves issuing a single command and configuring the config file if need be. There are GUI front ends to achieve the same. But we will just stick to the basic command line way to getting the update task done. The GUI is something you can figure out by yourself, so as usual we'll leave it for you to explore and have fun.

A group of packages are often put in a directory or a Web site called Repositories. The package manager looks for the repositories and installs the required applications from them. The repository itself can be downloaded and stored on the hard disk from where applications can be locally installed. Package managers can also be used to install applications from a package in which case the package manager will include the application in its database.