

yum. The commands are as follows:

Installing a new package : *apt-get install package*

Updating the package list : *apt-get update*

Update a package : *apt-get upgrade package*

Uninstalling a package: *apt-get remove package*

Adding Extra URLs: */etc/apt/sources.list* is the file where the address of repositories where packages can be looked for is stored. It is a simple file where sources are stored in each line. The first source(line) is looked for on priority, the second source (line) next and so on. You only need to add to this list the source from where you wish to update your packages.

The format to be followed is:

type uri arguments

Here, *type* specifies the packing type, which is usually deb for Debain based distros.

URI! is the Universal Resource Identifier, somewhat like a collection of URLs

Arguments are options such as stable/unstable which can be specified. In the Debian repository, only those directories specified in the arguments will be searched.

Example, the line *deb ftp://ftp.debian.org/debian stable contrib*, added to the *sources.list* file will look for the deb package in the ftp site *ftp.debian.org/debian* in the stable/contrib area.

Not specifying arguments will search the entire package list.

When looking for a package, you will also be find instructions on the updating you may need to do to the *sources.list* file.

The configurations and commands that can be used with the package managers is very vast and just as powerful. We have presented here only the basic of commands and setting which you may use to update packages on your system. For a detailed look into the other commands and options with the package managers you can use the *manual* command.

man yum or

man apt-get