

the compilation of the kernel. The steps for installation may vary a little depending on distribution.

Compiler Utilities

gcc - It is a compiler program for C

dev86 - 8086 based processor assembler/linker

cpp - GNU C compiler preprocessor

make - program to create executables

binutils - Library of binary utilities

Libraries

glibc-devel - Library files for standard header files for C

ncurses-5 - Screen handling package used mainly for CLI

ncurses-devel - for developing application that use ncurses.

Needed for menuconfig utility.

Rebuilding Kernel (Redhat)

1. `cd /usr/src/linux-2.*`

Stock kernel—if it exists else jump to 'New Compilation'

2. `edit Makefile`

Modify parameter *EXTRAVERSION=Rebuild*

3. `make mrproper`

Deletes the existing .config

4. `cp -p /usr/src/linux-2.* /configs/kernel-2.*-i686.config /usr/src/linux-2.*.config`

5. `make oldconfig`

To update .config with running kernel parameters

6. `make config / menuconfig` (for Text mode) / `xconfig`

7. `make dep`

8. `make clean`

9. `make bzImage`

Actual compilation process

10. `cp /usr/src/linux-2.* /arch/i386/boot/bzImage /boot/vmlinuz-2.*-Rebuild`

11. `cp /usr/src/linux-2.* /System.map /boot/System.map-2.*-Rebuild`

12. `cp /usr/src/linux-2.*.config /boot/.config-2.*-Rebuild`

13. Edit boot loader (either lilo.conf or grub.conf) to add entry for the rebuild kernel