

rent.

a) Prepare the file / files / folder

This step remains the same as in creating a tracker-based torrent. Collect all your files (or file) into a single folder. Make sure they are uncompressed, and fire up the BitTorrent client.



XXXXXXX

b) Create the torrent

In the BitTorrent program, click on File > Make torrent. Then press [Ctrl] + [N]. In the resulting dialog box, select the files you want to torrent. For this example, we will make a torrent of firefox.exe. The resulting screen will look like this.

Leave the piece size at 256KB. You can increase it if your file size is very large (hundreds of MBs). It is recommended to leave it at 256KB for smaller (10 to 20 MB) files. Check the "Use DHT" radio button and click Make. The torrent will be created and you will get a result screen as shown below.

Click the "Start seeding" button and you're done.

Like in the case of the tracker-based torrent, you should leave our client open for a sufficient length of time to reseed your torrent. However, discovering a tracker is a bit more difficult than tracker based torrents. There are two ways BitTorrent clients contact peers with trackers.

In the first method, a BitTorrent client will exchange information with other peers it contacts. During this process, each tracker-less torrent capable client will inform the other of its ability to host such torrents. These clients are known as seeders (or peers or users). DHT, which stands for Distributed Hash Table, is the method by which tracker-less torrents