

The “config.php” file is the mediator between vBulletin and your Web server. Any changes you want can be made here. Be careful though: we strongly advise you keep a backup of this file in case things go wrong.

Similarly, you can edit the *Technical Email Address*, *Master Database Server Name & Port*, and the *Master Database User Name and Password*. Note that we haven’t touched the “Slave Database Configuration,” assuming there’s a single backend database.

After editing, the config file has to be uploaded to your Web server. Using Smart FTP, which is a free software available from [www.download.com/3001-2160\\_4-10543387.html](http://www.download.com/3001-2160_4-10543387.html), you can simply drag or copy and paste the entire “upload” folder to your Web Server. After uploading, you can rename the “upload” folder on the Web Server to whatever you want.

We used vBulletin on the same machine, that is, our Web server and database server were the same. If you’re planning on doing something similar, all you need to do is copy the entire contents of the “upload” directory to the “www” folder in your PHP install directory.



Here’s what you get the first time vBulletin is run

Now we need to actually do the vBulletin setup, which will be accomplished by typing in the full path of the “install.php” file in your browser window. For the example, we have used we used “<http://localhost/VB/install/install.php>”; once the install file runs, you will have to enter your registration number, after which there are 12 easy-to-follow steps,



Step 3, showing the creating of the various tables used by vBulletin