

1. In your browser window address bar, type in “about:config”
2. In the filter option, type in “proxy”
3. In the search results, navigate to “network.proxy.no_proxies_on”
4. Double-click on this—you will see a box with one IP as a default value, typically 127.0.0.1. Add a comma and enter your own IP
5. You can now use your own IP address in the address bar.

Here’s a screenshot of about:config; highlighted is the network.proxy.no_proxies_on, the entry where the hosts IP address is to be added.



The about:config IP setting

Note that *about:config* only works with Mozilla and

Opera. IE users will need to go to Control Panel > Internet Options > Connections > LAN Settings > Bypass Proxy Server for Local Addresses. This entry should be checked.

Let’s get down to creating your very first code in PHP. Before we take the plunge, however, there are a few rules to remember.

1. The file containing the PHP code needn’t be an executable; rather, the .php extension does its magic here.
2. PHP looks for opening and closing tags to distinguish between PHP code and the rest of the html document. These start and stop tags are very simply “<?php”, which will cause *parsing* of any code found after it. Parsing is, very simply put, syntax analysis, and the program devoted to this task of analysing an input sequence in order to determine its grammatical structure is called a *parser*. The closing tag “?” will simply cause code placed after it to be treated as HTML, until, of course, another “<?php” is encountered. This makes PHP embeddable, and most Web pages contain PHP code embedded within the html document. You can also use short tags—just “<?” and “?”