

Create two new DWORD values, or modify the existing values, called `MaxConnectionsPerServer` and `MaxConnectionsPer1_0Server`. Change the values to equal the number of simultaneous requests allowed to a single HTTP server. The default values are 2 and 4 respectively. Restart Windows for the change to take effect.

By changing these settings you are causing Windows to break the HTTP protocol specification for any Internet applications running on your machine. Also, this affects all Windows Internet applications that use the standard API, including Internet Explorer.

Protect Against SYN Flood Attacks

Windows includes protection that allows it to detect and adjust when the system is being targeted with a SYN flood attack—a type of denial of service attack. When enabled, the connection responses time out more quickly in the event of an attack. (This value causes TCP to adjust retransmission of SYN-ACKS.)

Navigate to:

HLM\SYSTEM\CurrentControlSet\Services\Tcpip\Parameters

Create a new DWORD value called `SynAttackProtect` and set it to either 0, 1 or 2, based on the following.

0 (the default): Typical protection against SYN attacks

1: Better protection against SYN attacks that uses the advanced values mentioned below.

2 (the recommended value): Best protection against SYN attacks. This value adds additional delays to connection indications, and TCP connection requests quickly timeout when a SYN attack is in progress.

For extra control, you can create these additional DWORD values in the same key for each of the items below. They are not required for `SynAttackProtect` to be effective.