

**TcpMaxHalfOpen:** The default value is 100.

**TcpMaxHalfOpenRetried:** The default value is 80.

**TcpMaxPortsExhausted:** The default value is 5.

**TcpMaxConnectResponseRetransmissions:** The default is 3.

*When SynAttackProtect is using the best protection option, then Scalable windows and TCP parameters that are configured on each adapter (including Initial RTT and window size) are no longer available.*

## **Harden The TCP/IP Stack**

These following settings can be used to increase the ability of Windows to defend against Denial of Service attacks when connected directly to the Internet.

Navigate to:

HLM\SYSTEM\CurrentControlSet\Services\Tcpip\Parameters

Create the following DWORD values and set them as indicated.

### **EnableDeadGWDetect**

Set this to 0. The default is 1.

This disables dead-gateway detection as an attack could force the server to switch gateways.

### **EnableICMPRedirect**

Set this to 0. The default is 1.

This stops Windows from altering its route table in response to ICMP redirect messages. Some documentation has this listed as EnableICMPRedirects, but according to Microsoft it should be EnableICMPRedirect (with no “s”).

### **EnablePMTUDiscovery**

Set this to 0. The default is 1.

This disables maximum transmission unit (MTU) discovery as an attacker could force the MTU value to a very small value and overwork the stack.