

System State unless restoring to an alternative location”; click OK to overwrite. Click OK in the Confirm Restore dialog box. The restore operation will start showing you the progress of the restore. When it completes, click Close and accept the prompt to restart the computer.

2.2 Editing The Registry

Using Regedit you can add, delete, edit or rename a sub-key or value. Navigate to the appropriate section of the Registry that you wish to edit. This is similar to the folder and sub-folder concept in Explorer, and clicking on the hive’s “+” sign will make it expand to show the keys. Clicking on the “+” sign for each key will further expand them to show the sub-keys, and so on. If you are following instructions from a manual, the hive names are sometimes abbreviated as follows:

```
HKEY_CLASSES_ROOT: HKCR
HKEY_CURRENT_USER: HKCU
HKEY_LOCAL_MACHINE: HKLM
HKEY_USERS: HKU
```

Thus, the hive location `HKEY_CURRENT_USER\Control Panel\Accessibility\HighContrast` will be abbreviated as `HKCU\Control Panel\Accessibility\HighContrast`.

***Note:** In all the Registry hacks that begin in Chapter 4, we have used the following abbreviations:*

```
HKEY_CLASSES_ROOT: “HCR”
HKEY_CURRENT_USER: “HCU”
HKEY_LOCAL_MACHINE: “HLM”
```

Clicking on a key or sub-key will show, in the right pane, the values it holds. If it contains no values, at the minimum it will show a “(Default)” setting entry, which will not contain any data. Double-