

“Test” key in the specified path. To delete a value, put the hyphen symbol immediately after the equals sign of the data name. For example...

```
[HKEY_CURRENT_USER\Control Panel\Test]
“TestItem”=-
```

...will delete the TestItem data name in the Test sub-key of the Control Panel key in the HKEY_CURRENT_USER hive.

To rename an entry, first delete the entry using the above procedure, then specify the new name and values in the same .reg file. Both entries have to be separated by blank lines. An example:

```
[-HKEY_CURRENT_USER\Software\Yahoo\Pager\
IMVironments\baseball3]
```

```
[HKEY_CURRENT_USER\Software\Yahoo\Pager\IMVironme
nts\baseball4]
“promo”=dword:00000002
“name”=“Precious Moments”
```

```
[HKEY_CURRENT_USER\Software\Yahoo\Pager\IMVironme
nts\baseball4]
“promo”=dword:00000002
“name”=-
```

In this example, the sub-key “baseball3” will get deleted first. Then, the sub-key “baseball4” will be created with the data names “promo” and “name” containing a **DWORD** value of **00000002**, and a **String** value called “Precious Moments” respectively. Then the data name “name” will get deleted from the sub-key “baseball4”.

It is good practice to distribute your .reg file as a zipped archive to prevent accidental insertion into the Registry. Even though the user will be prompted before adding the .reg file to the registry,