

Navigate to:

HLM\SYSTEM\CurrentControlSet\Control\Session Manager\Memory Management\PrefetchParameters

The default value for the **EnablePrefetcher** setting is 3. Change this value to 5 to make applications load faster. You can experiment with higher values—up to 9—and see if you get a further improvement.

Name	Type	Data
(Default)	REG_SZ	(value not set)
EnablePrefetcher	REG_DWORD	0x00000001 (1)

HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Control\Session ...

Since this relates to the system, a reboot is required for the change to take effect.

Optimisation Of The Boot Files

Normal file fragmentation scatters the pieces of a file all over your hard disk. This invariably also affects the files that load at boot time. You can defragment the files that load at system startup to enable faster loading.

Navigate to:

HLM\SOFTWARE\Microsoft\Dfrg\BootOptimizeFunction

A setting called **Enable** under this key needs to be set to Y (for Yes). This setting defragments the boot files, and it *might* relocate startup files into contiguous clusters on the volume, reducing the movement of the disk head when reading the volume.

With the setting at Y, boot file optimisation occurs automatically if the system is idle for 10 minutes. A reboot is required for the change to take effect.

Name	Type	Data
(Default)	REG_SZ	(value not set)
Enable	REG_SZ	"Y"

HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Dfrg\BootOptimizeFunct...