

If the **DWORD AlwaysUnloadDLL** is not present, you will need to create it. Set the Value of the “(Default)” setting to **1**. Application-associated DLLs will get unloaded when the application is closed.

Run 16-bit Apps In Their Own Processes

Use this hack if you have more than one 16-bit application left over from the days of your nostalgia. XP runs all 16-bit applications in a single process. Having a separate process for each application can increase their stability and process.

Navigate to:

HLM\SYSTEM\CurrentControlSet\Control\WOW

Browse to the String **DefaultSeparateVDM**. If it's not there, you'll need to create it. Set its value to **Yes**.

Disable User Tracking

Useless to most users—except perhaps for system administrators—XP's inbuilt user tracking system uses up precious resources.

The system keeps track of the programs run by a user, the paths followed, and the documents used. (Did you know your XP was spying on you all this while?) Disable this to free up system resources.

Navigate to:

HCU\Software\Microsoft\Windows\CurrentVersion\Policies\Explorer

Set the **DWORD NoInstrumentation** to **1**. This will disable *most* of the user tracking features of XP.

Name	Type	Data
(Default)	REG_SZ	(value not set)
DisableThumbnailCache	REG_DWORD	0x00000001 (1)
HKEY_CURRENT_USER\Software\Microsoft\Windows\CurrentVersion\...		