

Navigate to:

HCU\Control Panel\Desktop

And to:

HKEY_USERS\DEFAULT\Control Panel\Desktop

Name	Type	Data
(Default)	REG_SZ	(value not set)
AutoEndTasks	REG_SZ	"1"
WaitToKillAppTimeout	REG_SZ	"10000"

The first key is user-specific, and the second is system-wide. In both these locations, change the String value called **AutoEndTasks** to **1** to kill the application immediately, or **0** to prompt for user action. **WaitToKillAppTimeout** controls the default time, in milliseconds, before killing the application. Reduce this time to further speed up the process.

Control Auto-Reboot After A Crash

When Windows crashes due to application, hardware or any other system fault, it is by default set to automatically reboot. In some cases, if the crashing is persistent and you want to troubleshoot your PC, you might not want the system to go into auto-reboot mode.

Name	Type	Data
(Default)	REG_SZ	(value not set)
AutoReboot	REG_DWORD	0x00000001 (1)

HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Control\CrashControl

Navigate to:

HLM\SYSTEM\CurrentControlSet\Control\CrashControl

Change the value of **AutoReboot** to **0** to prevent an automatic reboot after a crash.

Change Certain Folder Locations

Special folders such as My Documents, Desktop, and so on can be changed to any other location from that set by the default instal-