

the folders when the system restarts. A value of 1 should be specified if the folders are to be re-opened.

Name	Type	Data
(Default)	REG_SZ	(value not set)
PersonalBrowser	REG_DWORD	0x00000001 (1)
HKEY_CURRENT_USER\Software\Microsoft\Windows\CurrentVersion\...		

Hide Control Panel Applets

There are so many applets in the Control Panel that you never use! This hack will let you hide any of the applets in the Control Panel.

Name	Type	Data
(Default)	REG_SZ	(value not set)
fax.cpl	REG_SZ	"No"
powercfg.cpl	REG_SZ	"No"
HKEY_CURRENT_USER\Control Panel\don't load		

Navigate to:

HCU\Control Panel\don't load

(Yes, surprisingly, that key has an apostrophe!)

To hide the applets, you need to create a String Value for the filename of the applet in question, and set the value of the setting to No—or delete the key entirely to display the applet. The filenames of most of the common applets are as below, for quick reference. You might or might not find all the following on your system, and conversely, there could be applets on your system not mentioned here.

access.cpl - Accessibility Applet

appwiz.cpl - Add/Remove Programs Applet

console.cpl - Console Applet

timedate.cpl - Date and Time Applet

desk.cpl - Display Properties Applet

fax.cpl - Fax Applet