

These GUIDs should only be used on personal machines as their uniqueness cannot be guaranteed. GUIDs are usually generated by Windows, and not manually entered as we're doing here. If the GUID is distributed in runtime apps, there is the probability—however remote—of it clashing with the existing GUIDs.

For this example, we'll use a random GUID:

```
{FD4DF9E0-E3DE-11CE-BFCF-ABCD1DE12345}.
```

Hence, the key value will be:

```
HCR\CLSID\{FD4DF9E0-E3DE-11CE-BFCF-ABCD1DE12345}
```

Set the value of the “(Default)” setting for this key to the name of the folder—say “Digit Archive”. Create a new sub-key under the main key and call it “DefaultIcon”. That is, create a key called:

```
HCR\CLSID\{FD4DF9E0-E3DE-11CE-BFCF-ABCD1DE12345}\DefaultIcon
```

Set the value of the “(Default)” setting to the filename and path of the icon file you want to use for this folder. For example, “C:\digiticon.ico”, without the quotes. If you don't specify a path to an icon file, Windows will use its default folder icon.

Create another sub-key under the main key called “InProcServer32”, that is, create the key called:

```
HCR\CLSID\{FD4DF9E0-E3DE-11CE-BFCF-ABCD1DE12345}\InProcServer32
```

Set the “(Default)” setting here to “shell32.dll”. Create another String Value called **ThreadingModel**, with the value set to “Apartment”.

There's more! Create another sub-key called

```
HCR\CLSID\{FD4DF9E0-E3DE-11CE-BFCF-ABCD1DE12345}\Shell\Open My Folder\Command
```