

(Here, the “11.0” is for Office 2003; for Office XP and Office 2000, it’s 10.0 and 9.0 respectively.)

Here, find the **DWORD AcbControl** (or create it if it doesn’t exist.) Set it to **1**. (And to **0** later if you actually need to use multiple clipboards and want the dialog box.

Simply start (or restart) any Office application and the change will be effective.

Prevent Office Help From Stealing Space

This is a little weird—on some systems, the following doesn’t happen at all, and on some, it does. If Office resizes the main application window when you access the Help, you might want to turn off that behaviour.

While in an Office application, press [F1]. If your main window gets resized and you don’t like it...

Navigate to:

HCU\Software\Microsoft\Office\11.0\Common\HelpViewer

(Here, the “11.0” is for Office 2003; for Office XP and Office 2000, it’s 10.0 and 9.0 respectively.)

In all probability, a **DWORD IsFloating** won’t be present; create it and set its value to **1**. (If it’s already there, it’s probably set to **0**—reset it to **1**.)

To see the change, exit the Registry Editor and start (or restart) any Office program. Naturally, to reset what you’ve done, you can either delete the key or set it back to **0**.

Save To Where You Want To

You probably find the Places bar in XP very useful—the one that pops up when you do a **File > Save As** or a **File > Open** operation. You get My Documents, Desktop, and more. It’s so very conven-