

show either logical TRUE or logical FALSE after evaluating all these values in the function. Here is a brief overview of the functions.

- AND(logical1,logical2,...,logicaln): Verifies all the arguments and displays TRUE if all the results are logically true. If any of the arguments are not logically true, it will display FALSE.

Example: =AND(A3=B6,F5<>234)

Excel will here check to see if the values in A3 and B6 are equal, if they are not then Excel will display (return) the value FALSE. If A3 and B6 are equal, then Excel will evaluate the next argument. It will check to verify whether F5 is not equal to 234. If this is TRUE, then Excel will return the value TRUE. If it F5 is equal to 234, Excel will return FALSE.

- FALSE(): No arguments are used; this one just returns logical FALSE. Usually the FALSE() function is the result of a logical function (like AND, NOT, EQUALS etc) or used in combination with some other logical function.

Example: =IF (A3=FALSE,D5+25,D10=D5)

(See the IF function for an explanation)

- IF(logical_test,value_if_true,value_if_false): Checks the logical value of the first argument. If it is TRUE, Excel uses the second argument; if that one is not TRUE, then Excel uses the third argument.

Example: =IF (A3=FALSE,D5+25, D5+5)

If cell A3 has a value of FALSE, then add 25 to D5 and return the value. If A3 does not have a value of FALSE, then add 5 to D5 and return the value.

- IFERROR(value,value_if_error): Checks whether the first argu-