

ment is returns an error, if it is returns an error, it uses the value in the second argument, else it displays the first argument's value

Example: =IFERROR (A3/23,"Sorry! Non computable error!")

Divide cell A3 by 23. If the result is an error, then display the text "Sorry! Non computable error!", else display the result of the division

- NOT(logical): Checks if the argument is TRUE or FALSE. If TRUE, the value returned is FALSE. If FALSE, the value returned is TRUE.

Example: =NOT(A3=A4)

If "A3 is equal to A4" is TRUE, then the value returned will be FALSE. If A3 is not equal to A4, the value returned will be TRUE.

- OR(logical1,logical2,...logicaln): If any of the logical arguments are true, it returns the value TRUE; if all the arguments are false, it returns the value FALSE.

Example: =OR(A3=A4,B5<190)

If either A3 is equal to A4 or B5 is less than 190, then the value returned is TRUE. If A3 is not equal to A4 and B5 is equal to or greater than 190, the value returned is FALSE.

- TRUE() : No arguments are used; it just returns logical TRUE. Similar to the FALSE() function.

9.3 Date and Time Functions

Using date and time functions can becoming confusing if you do not understand how Excel treats dates and times internally. Externally, the data and time will be displayed in the human-friendly date/month/year format and its variations, and