

WEEKDAY(serial_no,return_type)

Example: WEEKDAY((DATE(07,03,25)),2)

The serial_no argument returns any day of the week between 1 and 7 or 0 and 6. The return_type argument is a number between 1 and 3. It specifies how the weekday should be handled. If the return_type is 1, then 1=Sunday and 7=Saturday. If the return_type is 2, then 1=Monday and 7=Sunday. If the return_type is 3, then 0=Monday and 6=Sunday. In the above example, we want to find out the day for the second return type where 1=Monday and 7=Sunday. The value returned will be 1.

MONTH(serial_no)

Example: MONTH((DATE(07,03,25)))

The serial_no argument returns any day of the month between 1 and 12. In the above example, the value returned will be 3.

YEAR(serial_no)

Example: YEAR((DATE(15,03,25)))

The serial_no argument returns any year between 1900 and 9999. Note that in the above example, the DATE function specifies the year as 15, which Excel will refer to recognise as 1915. If you want Excel to recognize 21st century years, you will need to enter the full year in the following format: YEAR((DATE(2015,03,25)))

DAYS360(start_date,end_date,method)

Example: DAYS360(A1,B2,FALSE)

This function calculates the number of days given the start_date

	B	C	D
1	End Date	DAYS360 - US	DAYS360 - European
2	23-Apr-07	23	23
3	31-Mar-07	2	1
4	31-Mar-07	0	0

The "DAYS360" function: difference between the US and European methods

argument and the end_date argument for a 360-day year where there are 12 months with 30 days each. The method argument specifies which calculation method to use: US or European. If using the