

htm for information on pricing and dealer locations.

The following are the specifications of Mac Pro, which can be customised at Apple's Web site:

Processing

- Two 2 GHz, 2.66 GHz, or 3 GHz dual-core Intel Xeon 5100 series processors
- Intel Core microarchitecture
- 4 MB shared L2 cache per processor
- 128-bit SSE3 vector engine
- 64-bit data paths and registers
- 1.33GHz, 64-bit dual independent frontside buses

Memory

- 667 MHz DDR2 ECC fully-buffered DIMM (FB-DIMM) memory
- 8 FB-DIMM slots on two memory riser cards (4 slots per card) supporting up to 16 GB of main memory
- Up to 256-bit wide memory architecture

Graphics and Displays

- Double-wide 16-lane PCI-Express graphics slot with one of the following graphics cards installed:
- NVIDIA GeForce 7300 GT with 256 MB of GDDR2 SDRAM, one single-link DVI port, and one dual-link DVI port
- ATI Radeon X1900 XT with 512 MB of GDDR3 SDRAM and two dual-link DVI ports
- NVIDIA Quadro FX 4500 with 512 MB of GDDR3 SDRAM, two dual-link DVI ports, and one stereo 3D port
- Multiple graphics card configurations including two, three, or four NVIDIA GeForce 7300 GT cards
- 300 W for up to four PCI-Express graphics cards
- Support for up to eight displays
- Support for digital resolutions up to 1920 x 1200; dual-link DVI ports support up to 2560 x 1600
- Support for analogue resolutions up to 2048 x 1536
- DVI to VGA Adapter included
- Dual-display support for extended desktop and video mirroring modes

Storage

- 4 independent 3 Gb/s Serial ATA cable-free, direct attach hard