

To customise the shortcut for any of these actions, just replace the text after the equal-to sign with the shortcut, keeping these rules in mind:

1. ~Accelerators~ like [Ctrl], [Shift] or [Alt] are represented with their names in lowercase - "control", "shift" and "alt" respectively
2. All other keys - letters, [Enter], [Space], the arrow keys and so on - are in uppercase. For example, "control alt ENTER", "shift DOWN" and so on.
3. Numbers remain as is, and function keys are represented as they are on the keyboard (F1, F3, etc.)

There's a lot more possible here: a lot of us prefer using bubbles for nodes to the default fork - you can enable this by changing the value of `standardnodestyle` from "fork" to "bubble." Just read through the file for more such nifty tweaks!

9.5.2 Changing the physical styles

We've talked about these before - physical styles are pre-configured formatting styles that you can apply to nodes using the function keys. To customise these, you need some knowledge of HTML font styles, and good old Notepad.

Open `patterns.xml` from your FreeMind installation directory (usually `C:\Program Files\FreeMind`), and you'll find a list of nodes of this nature:

```
<pattern name="Default">
  <node icon="none" color="#000000">
    <font>
  </node>
  <edge/>
</pattern>
```

The tags are quite self-explanatory: the `node` tag contains customisation for nodes - colours, font names and sizes and so on. For