

```
type="MAIL"/>
</inboxRepository>
```

SQL statements are used by James to access different types of vendor databases and perform various actions. These are detailed in the `sqlResources.xml` file in the `apps/james/conf` directory.

11.5 Security

Security is one of the most important facets of e-mail. James uses SSL or TLS for securing e-mails. This is possible through the use of the Java Secure Sockets Extension (JSSE) infrastructure, which is pre-packaged with Java 1.4.x.

To enable TLS in James for the SMTP server, modify the `<smtpserver>` element in the `config.xml` file so that it reads `<smtpserver - tls>`. Also set `<useTLS>` to `True`. The same procedure is to be followed for securing POP3, NNTP and RemoteManager. Here's how to enable TLS for SMTP. Remember that the port number and connection timeout can be changed, and you can set it according to how long (in milliseconds) you want to wait for a connection.

```
<smtpserver-tls enabled="true">
  <port>25</port>
  <useTLS>true</useTLS>
  <handler>
    <helloName autodetect="true"> myMailServer
  </helloName>
    <connectiontimeout> 360000 </connectiontimeout>
    <authorizedAddresses> 1211.0.0.0/8
  </authorizedAddresses>
    <maxmessagesize> 0 </maxmessagesize>
  </handler>
</smtpserver-tls>
```