

James can be configured for use as an authenticated SMTP server, where users need to authenticate themselves before sending mail. This prevents unauthorised e-mail and cuts down on the incidences of spam.

James also uses Bayesian filtering techniques to detect spam. Bayesian filters use message size as one of the metrics for determining whether a message is spam or not. The `BayesianAnalysisFeeder` maillet is used to send either ham (good mail) or spam messages to the `BayesianAnalysis` maillet. The frequency of spam, called the corpus, is stored in a JDBC database. This database is checked by a Java thread every 10 minutes for changes made to the corpus, which will then be updated if necessary. A `config.xml` definition example for deploying the feeder maillet which can be set to determine whether senders are spamming or hamming is shown below. These will be then stored in the database and James will block a blacklisted user the next time any mail from it is received. The `maxSize` attribute is "the maximum message size (in bytes) that a message may have to be considered spam," meaning that if a mail is larger than that, it will not be considered a candidate for being spam.

```
<!-- "not spam" bayesian analysis feeder. -->

<mailet match="RecipientIs=not.spam@thisdomain.com"
  class="BayesianAnalysisFeeder">
  <repositoryPath> db://maildb </repositoryPath>
  <feedType> ham </feedType>
  <maxSize> 200000 </maxSize>
</mailet>

<!-- "spam" bayesian analysis feeder. -->

<mailet match="RecipientIs=spam@thisdomain.com"
  class="BayesianAnalysisFeeder">
  <repositoryPath> db://maildb </repositoryPath>
  <feedType> spam </feedType>
```