

need to specify if you need to use a proxy server. If you connect to your ISP proxy server, you would check this box and fill in the proxy server name.

Here, we'd like to mention a powerful security feature built into FreeProxy called Local Binding. Selecting this ensures that only the specified adapter at the specified IP address can access the proxy. It goes like this: every physical network interface would have its own IP, and a dial-up connection would also be allocated an IP address. So by binding FreeProxy to only one network adaptor, you effectively prevent outsiders from accessing your internal network. However, this would probably not be of much use in the case of a non-fixed IP addresses.

Next, from Internet Options in the Windows Control Panel, you would need to check the Use Proxy Server for your LAN from the LAN Settings (from the Connections tab) and fill in the IP address of the server. You would also need to check the Bypass Proxy Server for Local Addresses box.

After specifying the port setup, you need to Click on RAS Settings and define the conditions for a Dial-Up Connection (DUN). Here, you would select the modem to use and fill in details such as username, password, and other options like connection timeout, auto-dial, etc.

12.2.3 Taking Control

Before you can allow people access to the network, you would first need to know who can be in and who shouldn't. These settings are defined in the User tab in the Define menu. By default, two groups of users are defined: All Users and Windows Authenticated Users.

Apart from this, you also have the option of adding individual users to the FreeProxy database. Groups have the added advantage of being to allocate permissions or resources for a large number of users who are part of that domain. For that to happen, though, the user needs to be authenticated. Put in plain English, what this