

the best option is to set it to run at a specific time when server load would be low.

The cache also lets you set limitations such as the maximum number of files to cache, lifetime of the cached files, and maximum size of the cache. Again, we feel it is necessary to only set a max cache size rather than specifying file number or age limitations.

### 12.3.4 Ban Lists

Perhaps one of the most significant upgrades to FreeProxy from v3.8x to v3.9x is the introduction of highly customisable ban lists. Simply put, a ban list is a list of all URLs or IP addresses that have been considered inappropriate and forbidden—online gambling sites, for instance. Of course, when it comes to an office network, it becomes all the more necessary to keep a tab on all such URLs, which would hog bandwidth without resulting in productive work (read: online games and social networking sites!).

FreeProxy allows the administrator to set up various categories of ban lists, each containing its own set of URLs to be banned and the response to be given for each category. These settings are saved to a file (.blf) and can be exported to other servers as well.

Click on the Ban-list icon to activate the feature. This takes you to the Manage Ban Lists window. Click New to create a new list. Once an active file is available, you can enter in various categories, their details, and how you want to ban them. FreeProxy allows you to ban each category differently—by either redirecting the browser to a different page or displaying the error page or simply giving a blunt response saying the page is banned.



Different categories of sites can be banned in different ways