

```
#acl    our_networks    src    192.168.1.0/24
192.168.2.0/24
#HTTP_access allow our_networks
acl my_network src 192.168.0.0/16
HTTP_access allow my_network
```

Finally, before you can start using Squid, you need to create the folders that would hold the cache files. Run Squid with the “-d -z” options. (A complete list of options available can be viewed by running Squid with the “-?” option.)



```
C:\WINDOWS\system32\cmd.exe
C:\squid\bin> squid -?
Usage: squid [-h|-k|-i|-n|-p|-s|-t|-v|-w|-x|-y|-z|-Z|-D|-F|-H|-O]
-h signal [-n name] [-o command-line]
-d level Write debugging to stderr also.
-f file Use given config-file instead of
    C:\squid\etc\squid.conf
-h Print help message.
-i Install as a Windows Service (see -n option).
-k reconfigure [-t] [-i] [-n] [-p] [-s] [-t] [-v] [-w] [-x] [-y] [-z] [-Z] [-D] [-F] [-H] [-O]
    Parse configuration file, then send signal to
    running copy (except -h parse) and exit.
-n name Specify Windows Service name to use for service operations
    default is: squid.
-p port Remove a Windows Service (see -n option).
-s [-l] [-l] facility
    Enable logging to syslog.
-u port Specify ICP port number (default: 3130), disable with B.
-v Print version.
-w Create swap directories.
-x Do not catch fatal signals.
-y Disable initial DNG tests.
-z Don't serve any requests until store is rebuilt.
-Z No daemon mode.
-D options
    Set Windows Service Command line options in Registry.
-E Do not set REENGINEER on port.
-F Double-check swap during rebuild.
-H Force full debugging.
-Y Only return UDP_HIT or UDP_MISS_NOFETCH during fast reload.
C:\squid\bin>
```

Squid presents quite a lot of options to set up

There, that should take care of the basics. There are still a lot of options and advanced features available, but they aren't essential and would be beyond the scope of this ~Fast Track~.

12.6.4 Get Ready, Go!

If you're running Windows 2000 or Windows XP, you can configure Squid to start as a service. For that, you first need to install Squid as a service on your server by running squid with the “-i” option. This basically adds some keys to your Registry and includes