

1.2.6 DIMM

Dual Inline Memory Module refers to the package in which RAM is available. Unlike the earlier and now obsolete SIMM (Single Inline Memory Module), a DIMM has contacts on both sides of the module.

1.2.7 DRAM

Dynamic RAM refers to volatile RAM that is constantly refreshed to prevent stored contents from being lost. All modern RAM is of this type, though there have been improvements. Data is stored in the form of rows and columns, with each storage area in RAM having a unique address that is a combination of the row and column number. DRAM was available in different types like SDRAM, EDO (Extended Data Out) RAM, FP (Fast Paging) RAM, and more, all of which are now obsolete except for SDRAM.

1.2.8 ECC RAM

An Error Correction Code (ECC) RAM module is a special type of module that includes additional components to verify the integrity of data stored in or transferred by system RAM. This is needed in critical systems that require high levels of data integrity, like servers.

1.2.9 RAS to CAS delay

This is the number of clock cycles that intervene between the identification of the row with the RAS and the start of launching the CAS. This is displayed as "tRCD" in the BIOS.

1.2.10 RAS Precharge Time

This is the number of cycles that are needed to refresh the RAS after the previous access before it can be used for a new access.

1.2.11 RDRAM

RAMBUS Direct RAM was based on a technology developed by RAMBUS. Unlike SDRAM, it used a serial mode of data transfer, and though the technology was considered superior to DDR SDRAM, its expensiveness made it unpopular. RDRAM modules are called RIMMs.