

colour difference signal (called the Pb/Cb component), and the red colour difference signal (called Pr/Cr). The value of the green signal can be calculated from the values of the blue and red signals, to reproduce the original image. Component video cables usually have three RCA plugs for each of the channels, as seen on DVD players. Component video offers better quality output than S-video and Composite video.

4.1.5 Composite Video

For regular TV broadcasting purposes, the video information in the three channels in Component video is fused into one and compressed. This is the Composite video signal.



Coaxial Cables

The fusion of the luminance and colour information channels cannot be accurately undone at the receiver's end, so there is a loss in quality. The composite video signal can be carried over a single cable. For TV broadcasts, the audio signals are also combined with the Composite video and transmitted through coaxial cables, the connectors for which are seen on all TVs. Composite video offers the lowest video quality compared to Component video and S-video.

4.1.6 Contrast Ratio

This refers to the difference in luminosity between the brightest and darkest modes of the display. If the contrast ratio is high, the on-screen images are clear even when ambient light is high.

4.1.7 CRT

In CRT displays, a beam of electrons is accelerated under high voltage and made to collide on a phosphor-coated screen. The particular phosphor elements that are hit by electrons are illuminated. In monochrome CRTs, each pixel is represented by a single phosphor element, while in colour CRTs, each pixel has three phosphors, each one capable of emitting red, green, and blue